

# SolarWinds.Hybrid-Cloud-Observability-Network-Monitoring.v2024-01-09.q70

<b>Exam Code:</b>	Hybrid-Cloud-Observability-Network-Monitoring
<b>Exam Name:</b>	Hybrid Cloud Observability Network Monitoring Exam
<b>Certification Provider:</b>	SolarWinds
<b>Free Question Number:</b>	70
<b>Version:</b>	v2024-01-09
<b># of views:</b>	588
<b># of Questions views:</b>	8515
<a href="https://www.freecram.net/torrent/SolarWinds.Hybrid-Cloud-Observability-Network-Monitoring.v2024-01-09.q70.html">https://www.freecram.net/torrent/SolarWinds.Hybrid-Cloud-Observability-Network-Monitoring.v2024-01-09.q70.html</a>	

## NEW QUESTION: 1

Flow data is not generating from a device in the web console. Wireshark was used to confirm the flows are being sent from the device to the poller and not blocked by the firewall. Why is the data not showing in the web console?

- A. flow monitoring was not enabled as device type in web console settings
- B. device is using IPv6 and HCO only supports IPv4
- C. missing source address field in flow configurations
- D. device is not monitored by hybrid cloud observability (HCO) features

**Answer:** ([SHOW ANSWER](#))

## NEW QUESTION: 2

Which two of the following locations can be checked for network hardware health functionality?  
(Choose two.)

- A. device view
- B. manage sensors
- C. node properties
- D. list resources

**Answer:** C,D ([LEAVE A REPLY](#))

## NEW QUESTION: 3

Which tool is used to establish flow alerts?

- A. create a flow alert panel
- B. flow alert wizard
- C. manage flow alert pane
- D. create alert flows

**Answer:** ([SHOW ANSWER](#))

**NEW QUESTION: 4**

On which two of the following occasions do custom pollers need to be created? (Choose two.)

- A. monitor equipment that does not support WMI
- B. monitor special equipment
- C. monitor unsupported object ID
- D. monitor specific metric that is not out-of-the-box

**Answer:** ([SHOW ANSWER](#))

**NEW QUESTION: 5**

When attempting to add universal device poller (UDP) results to a new chart widget, none of the custom poller results are displayed. If the web console switches to another view, the data appears in the chart. What is the most likely resolution?

- A. unassign and reassign custom poller in UDP application
- B. UDP application under web display, chart box must be checked for each view to be used
- C. UDP application, click transform results to convert them into a format viewable in a chart
- D. user does not have correct permissions to view the data

**Answer:** ([SHOW ANSWER](#))

**NEW QUESTION: 6**

Which two of the following actions can be taken to resolve unknown flow traffic events? (Choose two.)

- A. Configure devices to send all flow data.
- B. Add the devices and interfaces to SolarWinds' database.
- C. Enable automatic addition of flow sources.
- D. Ensure flow-enabled devices send data to appropriate port.

**Answer:** ([SHOW ANSWER](#))

**NEW QUESTION: 7**

A "no data" message is displayed in NetFlow charts. How can this be resolved?

- A. Confirm account has viewing permissions.
- B. Restart collector service.
- C. Shorten the time for view and resource.
- D. Refresh the current window.

**Answer:** ([SHOW ANSWER](#))

**NEW QUESTION: 8**

A network router node using ICMP polling has a green status icon and shows basic information (i.e., status) but is not showing more detailed statistics. What might resolve this issue?

- A. Edit the node properties to verify proper polling credentials.

- B. Run ping tests to verify communication.
- C. Switch polling to SNMP to gather additional polling statistics.
- D. Unmanage and re-manage the node.

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 9**

Which three of the following settings can be used to customize the thresholds for an object in SolarWinds' platform? (Choose three.)

- A. X of Y polls
- B. X concurrent polls
- C. single poll
- D. X consecutive polls

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 10**

Which two of the following flow sources are supported by hybrid cloud observability? (Choose two.)

- A. Cisco
- B. J-Flow
- C. cFlow
- D. NetStream

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 11**

In live mode, how frequently is log viewer data automatically refreshed?

- A. 10 minutes
- B. 1 minute
- C. 10 seconds
- D. 1 second

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 12**

A NetPath probe is to be built to monitor the paths between two sites. No Windows servers are available to run the agent. Which two of the following options can be used to set up the probe? (Choose two.)

- A. Install the agent on a red hat Linux server.
- B. Use the network device agent to run the probe from the router.
- C. Install the agent on a Windows 10 computer.
- D. Run the probe from the hybrid cloud observability (HCO) server.

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 13**

Which additional polling method is needed after adding an F5 load balancing node for SNMP monitoring?

- A. API
- B. CLI
- C. iControl
- D. WM1

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 14

If a NetFlow collector service is showing a "down" status, which two of the following steps are possible troubleshooting options? (Choose two.)

- A. Confirm the database connection is up and server has free resources.
- B. Start or restart SolarWinds' collector service.
- C. Delete and re-add NetFlow collector service.
- D. Start or restart SolarWinds' NetFlow service from Orion service manager.

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 15

What network capacity planning method is suitable for important devices and connections?

- A. peak calculation
- B. forecast calculation
- C. default calculation
- D. average calculation

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 16

A device studio poller is being built for the node details widget. The plan is to add a field for serial numbers.

How would this be accomplished?

- A. Add the object ID (QID) to an existing data source and edit the field name in the widget.
- B. Create a serial number universal device poller (UDP) and link to the node details widget.
- C. Default widgets are being used, fields cannot be added to the device studio
- D. Change one data source field to serial number and supply the OID for the data source.

Answer: ([SHOW ANSWER](#))

**Valid Hybrid-Cloud-Observability-Network-Monitoring Dumps** shared by ExamDiscuss.com for Helping Passing Hybrid-Cloud-Observability-Network-Monitoring Exam! ExamDiscuss.com now offer the **newest Hybrid-Cloud-Observability-Network-Monitoring exam dumps**, the ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring exam

**questions have been updated and answers have been corrected** get the **newest** ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring dumps with Test Engine here: <https://www.examdisscuss.com/SolarWinds/exam/Hybrid-Cloud-Observability-Network-Monitoring/premium/> (152 Q&As Dumps, **35%OFF** Special Discount Code: **freecram**)

#### **NEW QUESTION: 17**

Which option is available when choosing the collect Windows events without an agent so that Windows event logs can be recognized?

- A. Convert Windows events to svlog with SolarWinds event log forwarder.
- B. Convert Windows events to VMware with SolarWinds event log forwarder.
- C. Convert Windows events to log files with SolarWinds event log forwarder.
- D. Convert Windows events to traps with SolarWinds event log forwarder.

**Answer: ([SHOW ANSWER](#))**

#### **NEW QUESTION: 18**

Through which means does NetFlow traffic analysis (NTA) process flow data?

- A. agent
- B. polling method
- C. collector
- D. configuration

**Answer: ([SHOW ANSWER](#))**

#### **NEW QUESTION: 19**

What is a possible result of decreasing the top talking optimization value?

- A. reduced database performance
- B. slower reporting speed
- C. reduced page load times
- D. increased storage requirement

**Answer: ([SHOW ANSWER](#))**

#### **NEW QUESTION: 20**

How does data collection with a flow collector differ from data collection with a polling engine?

- A. flow collector is a type of polling engine for flow data
- B. flow data is processed by flow collector or polling engine
- C. flow data is collected by flow collector and processed by polling engine
- D. source devices must be configured to send their data to a flow collector

**Answer: ([SHOW ANSWER](#))**

#### **NEW QUESTION: 21**

The unclassified traffic in the web console has been identified as MSSQL traffic. It is known as an application mapping that hybrid cloud observability maps by default. Which two of the following reasons explain why the traffic is showing as unclassified? (Choose two.)

- A. The version of MSSQL being used is not supported.
- B. A different port is being used.
- C. A firewall is blocking the traffic.
- D. The source or the destination port field is not present.

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 22

Which switch model is supported in network insight?

- A. Brocade G620
- B. Juniper EX
- C. Meraki MX
- D. Cisco Nexus

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 23

Which two of the following functions are tied to SolarWinds' MIB database? (Choose two.)

- A. SolarWinds' MIB database defines what kind of pollers can be built for the metric.
- B. aSolarWinds' MIB database updates OIDs on the device during the polling process.
- C. SolarWinds' MIB database maps object IDs (OIDs) to their textual names.
- D. SolarWinds' MIB database enables automatic polling of devices.

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 24

Upon examining bandwidth utilization, it is confirmed that the total utilization and flow numbers do not match. What is the likely cause?

- A. flows do not contain all traffic in bandwidth numbers
- B. a firewall is blocking the data flow configuration
- C. receivingboth IPv4 and IPv6 flows and not all are counted in total bandwidth
- D. SNMP bandwidth numbers for the interface need to be adjusted in the console

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 25

Several resources are showing duplicate flow data. What is the most likely cause?

- A. SolarWinds' NetFlow service needs to be restarted
- B. interfaces have duplicate entries in flow sources management
- C. interfaces in flow sources management are set to drop
- D. source devices are configured to export flow data on ingress and egress

Answer: D ([LEAVE A REPLY](#))

**NEW QUESTION: 26**

What is the maximum number of resources that can be displayed in flow charts created by SolarWinds' platform views?

- A. 25
- B. 75
- C. 50
- D. 100

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 27**

A universal device poller (UDP) was created on the main polling engine to collect CPU temperature for routers polled by the main polling engine and switches polled by the additional polling engine. It is noted that statistics from the switches are missing.

What is the likely cause of the missing statistics?

- A. UDPs do not work with additional polling engines
- B. routers are not monitored on the additional polling engine
- C. switches are not monitored in the additional polling engine
- D. UDPs are tied to polling engine on which they are hosted

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 28**

Which port needs to be open in order to analyze flow and monitor CBQoS?

- A. Flow (SNMP, 161), CBQoS (TCP, 2055)
- B. Flow (TCP, 2055), CBQoS (SNMP, 161)
- C. Flow (SNMP, 161), CBQoS (UDP, 2055)
- D. Flow (UDP, 2055), CBQoS (SNMP, 161)

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 29**

An agent is deployed to the Windows server in order to monitor logs, however logs are not coming in from the related agent. It is confirmed that the agent software is deployed and installed on the target machine.

What additional setting needs to be checked?

- A. polling method is set to agent
- B. log forwarding feature is enabled
- C. polling method is set to WMI
- D. correct rule to read logs is configured

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 30**

Upon logging into the web console to check node statuses, it is noted that several nodes display a "down" status when they are up and running. Which two of the following situations are the likely causes of this issue?

(Choose two.)

- A. nodes using incorrect SNMP credentials
- B. polling interval set to value other than default
- C. node status must be set to auto management
- D. ICMP blocked from polling engine to target node

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 31

The below error message is received.

NetFlow Receiver Service [SERVERNAME] is receiving a NetFlow data stream from an unmanaged device (x.x.x.x). The NetFlow data stream from x.x.x.x will be discarded

How should this error be resolved?

- A. only IP flow ingress applied on interfaces
- B. ensure the collector service is up
- C. change the IP address on the node or enable "allow matching nodes by another IP"
- D. ensure the device is configured to send flow data to hybrid cloud observability (HCO)

Answer: ([SHOW ANSWER](#))

**Valid Hybrid-Cloud-Observability-Network-Monitoring Dumps** shared by ExamDiscuss.com for Helping Passing Hybrid-Cloud-Observability-Network-Monitoring Exam! ExamDiscuss.com now offer the **newest Hybrid-Cloud-Observability-Network-Monitoring exam dumps**, the ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring exam **questions have been updated** and **answers have been corrected** get the **newest** ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring dumps with Test Engine here: <https://www.examdiscuss.com/SolarWinds/exam/Hybrid-Cloud-Observability-Network-Monitoring/premium/> (152 Q&As Dumps, **35%OFF** Special Discount Code: **freecram**)

#### NEW QUESTION: 32

Which SNMP version will support MD5, SHA1, SHA256, and SHA512 authentication in SolarWinds' platform?

- A. version 1
- B. version 2c
- C. version 2
- D. version 3

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 33**

Which status rollup mode displays groups defined as collections of redundant or backup devices?

- A. showzero
- B. show worst
- C. show mixed
- D. show best

**Answer: ([SHOW ANSWER](#))**

**NEW QUESTION: 34**

In setting up a storage and search retention period for log analyzer, what is the default retention period?

- A. 21 days
- B. 24 hours
- C. 31 days
- D. 7 days

**Answer: ([SHOW ANSWER](#))**

**NEW QUESTION: 35**

A node has been added to hybrid cloud observability and shows an "unknown" status until the data is polled.

The default interval for polling status is two minutes.

If the node stays in the "unknown" status longer than the polling interval, which three of the following steps can be performed to resolve the issue? (Choose three.)

- A. Run SNMP walk on the appropriate node.
- B. Ping device from assigned polling engine.
- C. Verify a pingresponsefor this node is received through the ICMP.
- D. Verify the appropriate polling method is set for this node.

**Answer: ([SHOW ANSWER](#))**

**NEW QUESTION: 36**

Which two of the following tasks must be accomplished to monitor servers and connections in a load-balancing environment? (Choose two.)

- A. add Cisco Nexus device in network device configuration manager
- B. enable CLI polling
- C. add Cisco Nexus device in network health / performance monitoring
- D. enable F5 iControl polling

**Answer: ([SHOW ANSWER](#))**

**NEW QUESTION: 37**

Which two of the following services can be monitored in network insight with network health, performance monitor, and NCM features installed in hybrid cloud observability? (Choose two.)

- A. global protect VPN
- B. access lists
- C. policy details
- D. high availability details

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 38

A node is being polled. The only data visible is response time and packet loss. Detailed statistics are needed.

How should this issue be resolved?

- A. switch polling method from SNMP to ICMP
- B. switch polling method from SNMP to API
- C. switch polling method from WMI to SNMP
- D. switch polling method from ICMP to SNMP

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 39

If an IP address group is hidden in IP address groups management, what impact will it have on the data?

- A. group will not be shown in IPAM
- B. group will be shown in compliance reports
- C. group will not be shown in charts or reports
- D. group historical data will be deleted

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 40

If the data collected for hardware health is incorrect, which step could rectify the issue?

- A. Download the MIB file from the SolarWinds website and add it to the device's firmware.
- B. Create a custom poller in device studio for fan speed, power supply, and temperature.
- C. Change the poller assigned to sensor.
- D. Change the MIB tree used for polling.

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 41

Which two of the following requirements are needed to set up network devices and export NetFlow data?

(Choose two.)

- A. Each device can be optionally configured to export NetFlow data to SolarWinds' NTA.
- B. The interface through which a device exports NetFlow data must be monitored in NPM.

- C. Each device that exports NetFlow data to SolarWinds' NTA must be monitored in NCM.
- D. Each device that exports NetFlow data to SolarWinds' NTA must be monitored in NPM.

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 42**

In which two of the following cases does duplicate flow data occur? (Choose two.)

- A. IP flow ingress on some interfaces and egress on others
- B. both IP flow ingress and egress applied on one interface
- C. IP flow ingress applied on all interfaces, no egress usage
- D. both IP flow ingress and egress applied for all interfaces

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 43**

Which tool in the web console will verify the object ID (OID) being used is a match for the node being created for a custom poller?

- A. firmware repository
- B. MIB browser
- C. CLI settings
- D. component library

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 44**

What is needed to edit trigger conditions in flow alerts?

- A. Python
- B. PowerShel
- C. SVVQL
- D. SQL

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 45**

When creating a new rule action, what is the best option to enable if too many events trigger the rule within a short time?

- A. excessive event
- B. flood protection
- C. entry count
- D. time window

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 46**

What is required to submit an MIB database update request to SolarWinds?

- A. SNMP or MIB walk from the device

- B. type of widget to populate data
- C. specific object ID (QID) for polling
- D. polling interval to monitor the metric

**Answer:** ([SHOW ANSWER](#))

**Valid Hybrid-Cloud-Observability-Network-Monitoring Dumps** shared by ExamDiscuss.com for Helping Passing Hybrid-Cloud-Observability-Network-Monitoring Exam! ExamDiscuss.com now offer the **newest Hybrid-Cloud-Observability-Network-Monitoring exam dumps**, the ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring exam **questions have been updated** and **answers have been corrected** get the **newest** ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring dumps with Test Engine here: <https://www.examdiscuss.com/SolarWinds/exam/Hybrid-Cloud-Observability-Network-Monitoring/premium/> (152 Q&As Dumps, **35%OFF** Special Discount Code: **freecram**)

**NEW QUESTION: 47**

From which two of the following locations can the status of the flow collector service be checked? (Choose two.)

- A. top XX receivers
- B. flow and CBQoS sources
- C. NetFlow settings
- D. NetFlow collector services

**Answer:** ([SHOW ANSWER](#))

**NEW QUESTION: 48**

Which three of the following steps should be taken to troubleshoot a 'test failed' result for SNMP nodes in hybrid cloud observability? (Choose three.)

- A. Add remote site node and confirm firewall rules are configured to allow SNMP traffic.
- B. Verify the node can be pinged from the application server.
- C. Confirm the use ofSNMPv3 with authentication keys.
- D. Verify the SNMP service on the node has been restarted after changing the community string.

**Answer:** ([SHOW ANSWER](#))

**NEW QUESTION: 49**

A poller is to be built that will add two values together to show a single value in the web console using the universal device poller (UDP) tool. How would this be accomplished?

- A. UDP tool does not support more than one OID per poller, another tool is needed
- B. build a poller for each OID then use transform results to combine values from the two pollers
- C. add both object IDs (OIDs) to the poller and combine values in a single value for the web console

D. UDP tool does not support more than one OID per poller, another OID is needed

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 50**

On which two of the following port does log analyzer listen for TCP syslog messages? (Choose two.)

- A. 162
- B. 514
- C. 6514
- D. 1463

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 51**

Which two of the following requirements are needed to monitor an application on a server? (Choose two.)

- A. Click the monitor recommendation applications button.
- B. Add application and ports using server as source and destination IP addresses.
- C. Add the IP address of the server into an IP address group.
- D. Find the application to monitor in the list of available applications and enable it.

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 52**

Which statement is true regarding universal device pollers (UDP)?

- A. poll multiple object IDs (QIDs) for a given technology
- B. polled values are displayed in dedicated resources
- C. perform operations /transformations on polled data
- D. polled values are displayed in existing resources

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 53**

When a parent object goes down or becomes unresponsive, all interfaces on the switch will also be unresponsive. Though they may be working, "unreachable" status is used because the parent node reports as

"down" and a status cannot be determined. Any alerts where the trigger condition includes node status equal to

"down" are not triggered.

In which section of SolarWinds' platform can an administrator configure the status of child objects as

"unreachable" instead of "down" or "unknown"?

- A. core thresholds
- B. polling settings
- C. manage dependencies

D. node status participation

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 54**

Which SNMP version allows usernames and passwords?

- A. version 4
- B. version 1
- C. version 2c
- D. version 3

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 55**

Which two of the following tools are available for troubleshooting network node connectivity issues? (Choose two.)

- A. network insight
- B. NetPath
- C. asset inventory
- D. MIB browser

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 56**

The status of the interfaces for a network switch shows as "unknown" in SolarWinds' platform web console, although the node status is "up". What could be the reason?

- A. interfaces are not managed in hybrid cloud observability (HCO)
- B. ICMP is blocked between the node and the polling engine
- C. hardware sensors are disabled on the node
- D. interface details have changed on the device

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 57**

Which two of the following effects would apply to a situation where a NetPath probe polling interval is increased to 15 minutes from the default value of 10 minutes? (Choose two.)

- A. accuracy is increased
- B. accuracy is decreased
- C. probe is more likely to show all routes
- D. probe will not complete successfully

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 58**

SNMP traps are being received from several devices. While most of the traps are normal, traps from one of the devices contain fields that are unreadable. The device is not being monitored in any other way. Which two of the following points should be checked? (Choose two.)

- A. Verify the device supports hybrid cloud
- B. Verify the device supports SNMP and is added as a node.
- C. Verify the device is not usingSNMFV3 and is added as a node.
- D. Verify the device's MIBfile is in SolarWinds' MIB database.

**Answer:** ([SHOW ANSWER](#))

#### **NEW QUESTION: 59**

What is the default amount of historical data needed for calculating capacity forecast?

- A. 7 to 30 days
- B. 7 to 180 day
- C. 1 to 90 days
- D. 1 to 30 days

**Answer:** ([SHOW ANSWER](#))

#### **NEW QUESTION: 60**

On a single node, one or more interfaces are showing an "unknown" status. What is the best way to resolve the issue?

- A. Delete and re-add the affected interfaces.
- B. Change node's pollingmethod to ICMP.
- C. Delete and rediscover the node showing affected interfaces.
- D. Verify the interfaces are assigned to SolarWinds' native poller.

**Answer:** A ([LEAVE A REPLY](#))

#### **NEW QUESTION: 61**

It is noted in flow source view that some devices are showing "never received" in the last received flow column. It is verified that the flows are not being blocked by a firewall. What is the likely cause?

- A. a primary field of data is missing and being dropped
- B. flows are IPv6 and not supported by the network monitoring features
- C. node is no longer monitored by the monitoring features
- D. interface is no longer monitored by the network monitoring features

**Answer:** ([SHOW ANSWER](#))

**Valid Hybrid-Cloud-Observability-Network-Monitoring Dumps** shared by ExamDiscuss.com for Helping Passing Hybrid-Cloud-Observability-Network-Monitoring Exam! ExamDiscuss.com now offer the **newest Hybrid-Cloud-Observability-Network-Monitoring**

**exam dumps**, the ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring exam questions have been updated and answers have been corrected get the newest ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring dumps with Test Engine here: <https://www.examd Discuss.com/SolarWinds/exam/Hybrid-Cloud-Observability-Network-Monitoring/premium/> (152 Q&As Dumps, **35%OFF** Special Discount Code: **freecram**)

#### **NEW QUESTION: 62**

A universal device poller (UDP) is being built for a metric to monitor in a radial gauge of a web console.

When a gauge resource in the poller is to be selected, it is found that the resource is grayed out. What could be causing this?

- A. object ID (OID) polled does not support radial gauge.
- B. OID polled is not supported by the device.
- C. OID polled is not in current MIB file of MIB database.
- D. UDP does not support gauges to display polled information.

**Answer: A** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 63**

A network discovery profile for a network area completes with most devices discovered, except for a few SNMP enabled network devices. These undiscovered devices are verified to be operational and respond to SNMP queries.

What could be the cause?

- A. device MIB is not in SolarWinds' MIB database
- B. discovery timeout value is set too low
- C. SNMP community strings in profile are invalid
- D. no SNMP pollers match the device

**Answer: (**[SHOW ANSWER](#)**)**

#### **NEW QUESTION: 64**

If an SNMP community string is changed on a device, which two of the following steps are required to re-establish successful polling on the node? (Choose two.)

- A. Delete and add the node back into the platform.
- B. Edit the node properties and save the changes.
- C. Restart the SNMP service on the source device.
- D. Update the community string in node properties.

**Answer: (**[SHOW ANSWER](#)**)**

#### **NEW QUESTION: 65**

SNMP get type defines the SNMP polling method used by a universal device poller (UDP) to get the device's object ID (OID) values.

Which SNMP get type retrieves values from a particular column?

- A. table
- B. data
- C. next
- D. column

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 66**

In which scenario would the device studio poller tool be considered the best tool for building a required poller?

- A. Building a poller to monitor VPN tunnel status.
- B. Building a poller to show CPU and memory status.
- C. Building a poller for ARP tables to display in the web console.
- D. Building a poller to add missing information to node details.

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 67**

What is the default amount of historical data needed for calculating capacity forecast?

- A. 7 to 180 day
- B. 1 to 90 days
- C. 7 to 30 days
- D. 1 to 30 days

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 68**

Probing interval determines how often and how long information is polled from the network path. Which two of the following statements are true regarding probing intervals? (Choose two.)

- A. probing more frequently allows the data to update faster but decreases data accuracy
- B. probing less frequently allows the data to update more slowly and increases data accuracy
- C. probing less frequently allows the data to update faster but decreases data accuracy
- D. probing more frequently allows the data to update more slowly and increases data accuracy

Answer: A,B ([LEAVE A REPLY](#))

**NEW QUESTION: 69**

What is the minimum amount of RAM required for setting up log collection in hybrid cloud observability?

- A. 4 GB
- B. 32 GB
- C. 16 GB
- D. GB

Answer: ([SHOW ANSWER](#))

**NEW QUESTION: 70**

Which custom filter allows a user to view specific statistics about an entire network and its devices without having to navigate through the web console by single-device views?

- A. flow alert
- B. top 10 applications
- C. flow navigator
- D. NBAR2

**Answer: ([SHOW ANSWER](#))**

**Valid Hybrid-Cloud-Observability-Network-Monitoring Dumps** shared by ExamDiscuss.com for Helping Passing Hybrid-Cloud-Observability-Network-Monitoring Exam! ExamDiscuss.com now offer the **newest Hybrid-Cloud-Observability-Network-Monitoring exam dumps**, the ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring exam **questions have been updated** and **answers have been corrected** get the **newest** ExamDiscuss.com Hybrid-Cloud-Observability-Network-Monitoring dumps with Test Engine here: <https://www.examdiscuss.com/SolarWinds/exam/Hybrid-Cloud-Observability-Network-Monitoring/premium/> (152 Q&As Dumps, **35%OFF** Special Discount Code: **freecram**)